



AVN252 Outdoor H.264 IR Network Camera



FEATURES

- True Day & Night surveillance with IR shifter & large aperture lens (F1.4)
- The best cost / performance outdoor solution with IP67
- Longer IR effective distance up to 40 meters
- High resolution with the best video performance
- Smart Light Control to avoid overexposure
- Excellent outdoor ID design with cable management
- Free CMS software
- Durable 56 IR LEDs built-in application

SPECIFICATIONS

AVN252

AVN252	
■ Network	
Network Compression	H.264
LAN Port	YES
LAN Speed	10/100 Based-T Ethernet
Supported Protocols	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP, RTSP
Frame Rate	NTSC: 30, PAL: 25
Number of Online Users	10
Security	Multiple user access levels with password protection
Web management	The licensed software "Video Viewer" for up to 16 network cameras control simultaneously
■ Camera	
Image Sensor	1/3" HR color CCD image sensor
Pixels	768(H) x 494(V) <NTSC> / 752(H) x 582(V)) <PAL>
Min Illumination	0.3 Lux / F1.4, 0 Lux (IR ON)
Shutter Speed	1 / 60 (1/50) to 1 / 100,000 sec.
S/N Ratio	More than 48dB (AGC off)
Lens	f6.0mm
Viewing Angle	48°
IR LED	56 units
IR Effective Range	Up to 40 meters



SPECIFICATIONS (CONTINUED)

AVN252	
IR Shift	YES
Smart Light Control	YES
White Balance	ATW
AGC	Auto
IRIS Mode	AES
IP Rating	IP67
Power Source ($\pm 10\%$)	Dc12V
Operating Temperature	0°C~40°C
■ Others	
Remote Control	YES
Motion Detection	YES
Alarm and event Notification	Image upload over FTP and Email
Minimum Web Browsing Requirements	<ul style="list-style-type: none">• Pentium 4 CPU 1.3 GHz or higher, or equivalent AMD• 256 MB RAM• AGP graphics card, Direct Draw, 32MB RAM• Windows Vista, XP, Windows 2000 Server, ME, 98, DirectX 9.0 or later• Internet Explorer 6.x or later

* The specifications are subject to change without notice.

** Dimensional tolerance: ($\pm 5\text{mm}$)