

CPC329A

Dome Camera



● Product Overview

This mini dome camera employs 1/3" Sony Super HAD CCD image sensor and can be easily installed at any places for users to monitor a wider area.

● Features

- 1/3" SONY Color Super HAD CCD image sensor to provide superior images
- Satisfied min. illumination of 0.5 Lux/F2.0
- Built-in Auto Electronic Shutter
- Signal-to-Noise ratio is more than 48dB

● Specification

	CPC329A
Pick-up Element	1/3" SONY Color Super HAD CCD image sensor
Resolution	Standard
Min. Illumination	0.5Lux / F2.0
Number of Pixel	512(H)x492(V) <NTSC> / 512(H)x582(V) <PAL>
S/N Ratio	More than 48dB (AGC off)
Iris Mode	AES
Electronic Shutter	1/60 (1/50) to 1/100,000 sec
White Balance	ATW
BLC	ON
AGC	MAX
Lens	f3.6mm/ F2.0
Video Output	1.0Vp-p composite, 75Ω
Microphone	YES
Power Source	DC12V±10%
Current Consumption	105mA ± 10%
Operating Temperature	0°C ~40 °C (32°F ~104°F)
Dimension (mm)	104(Ø) x 60(H)
Gross Weight	210g

* This specification is subject to change without notice.