

EN-DVJ30-70

700TVL· AI-Alloy IR Dome Camera · Product SPEC



EN-DVJ30-70

- ◆ AI-Alloy IR Dome Camera With OSD
- ◆ Higt Resolution 650/700TVL
- ◆ 2D-DNR/BLC/MD/Privacy Masking
- ◆ 3-Axis Bracket, Easy for Installation
- ◆ 36pcs of \varnothing 5 IR leds, IR Range 30M



Image Device	1/3" Exview HAD CCD II (ICX672/3AKA)
DSP Device	Effio-E (CXD4127GG,CXD4816GG)
Resolution	Color Mode: 650TVL; B/W Mode:700TVL
Picture Elements	PAL:976(H)×582(V) NTSC:976(H)×494(V)
IR Led & IR Range	36pcs of \varnothing 5 IR leds, IR Range 30M
Min. Illumination	0.001 Lux (F2.0)/ 0 Lux IR On
Lens Furnished	4-9mm Manual Zoom Lens (2.8-12mm is Optional)
TV System	PAL/NTSC
Electronic Shutter	NTSC:1/60~1/100,000, PAL:1/50~1/110,000
S/N Ratio	More than 52dB
Gamma	0.45
Exposure	Auto
Shuter/ AGC	Auto/Manual
White Balance	ATW / User1/User2
Backlight	OFF/ON/BLC/ HLC
Pict Adjust	Mirror/Brightness/Contrast/Sharpness/Hue/Gain
ATR	ON/OFF
Motion Det	OFF/ON(Detect sense/ Area Sel)
Peivacy Masking	OFF/ON (4 Zone)
Day/Nigh	True Day and Night (Auto/ Day / Night / Ext. D&N)
2D-NR	OFF/ON (Y/C level)
Camera ID	OFF/ON
Sync. System	Internal
Video Output	1 Vp-p / 75 Ohms
Power Supply	DC12V±10%
Operation Temperature	-10℃ ~ +50℃ RH95% Max
Dimension	Body : \varnothing 120x120mm With Bracket: \varnothing 120x290mm
Weight	1.6kg