

EN-VI50K70

700TVL · Weatherproof IR Camera · Product SPEC



EN-VI50K-70

- ◆ Weatherproof IR Camera With OSD
- ◆ High Resolution 650/700TVL
- ◆ 2D-DNR/BLC/MD/Privacy Masking
- ◆ 3-Axis & Hidden Cable Bracket
- ◆ 72pcs of ϕ 5 IR leds, IR Range 50M



Image Device	1/3" Exview HAD CCD II (ICX672/3AKA)
DSP Device	Effio-E (CXD4127GG, CXD4816GG)
Resolution	Color Mode: 650TVL; B/W Mode: 700TVL
Picture Elements	PAL: 976(H) × 582(V) NTSC: 976(H) × 494(V)
IR Led & IR Range	72pcs ϕ 5 IR Led; 50M IR Distance
Min. Illumination	0.001 Lux (F2.0)/ 0 Lux IR On
Lens Furnished	4-9mm Manual Zoom Lens (2.8-12mm is Optional)
TV System	PAL/NTSC
Electronic Shutter	NTSC: 1/60 ~ 1/100,000, PAL: 1/50 ~ 1/110,000
S/N Ratio	More than 52dB
Gamma	0.45
Exposure	Auto
Shutter/ AGC	Auto/Manual
White Balance	ATW / User1/User2
Backlight	OFF/ON/BLC/ HLC
Pict Adjust	Mirror/Brightness/Contrast/Sharpness/Hue/Gain
ATR	ON/OFF
Motion Det	OFF/ON (Detect sense/ Area Sel)
Privacy Masking	OFF/ON (4 Zone)
Day/Night	True Day and Night (Auto/ Day / Night / Ext. D&N)
2D-NR	OFF/ON (Y/C level)
Camera ID	OFF/ON
Sync. System	Internal
Video Output	1 Vp-p / 75 Ohms
Power Supply	DC12V ± 10%
Operation Temperature	-10°C ~ +50°C RH95% Max
Dimension	Body : ϕ 96x187mm With Bracket: 260(L)x101(W)x96(H)
Weight	1.6kg