

WIT1010s

VANDAL RESISTANCE VARI-FOCAL DOME CAMERA



Features:

- High sensitivity, true colour, high resolution
- Hi-impact reinforced Polycarbonate Armor Dome withstand a blow 10-pound sledgehammer
- 480 TVL 1/3" Sony super HAD sensor
- Min Illumination up to 0.1 Lux with IR light sensing response
- Auto Electronic Shutter, Rang: 1/50(1/60) – 1/100,000 sec
- Reinforced polycarbonate with special coating on surface
- Max. Load 500 Kg deformation without crack
- Die-Casting Base: Ultra hard aluminium with painting finish

Specifications

| | |
|---------------------------------|---|
| Picture Elements HxV | NTSC/EIA: 768*494; PAL/CCIP: 753*582 (High) |
| H.Sync Frequency | NTSC: 15.734 KHz, PAL: 15.625 KHz |
| V. Sync Frequency | NTSC: 59.94 Hz, PAL: 50 Hz |
| Chips | 1/3" Sony |
| Lens(mm) | Vari-Focal 4mm-9mm |
| Min Illumination | 0.1 Lux |
| Resolution | 480 TV Line |
| Synchronization | Internal |
| White Balance | Auto White Balance |
| Electronic Shutter | Auto, Rang: 1/50(1/60) – 1/100,000 sec |
| Gain control | Auto |
| Gamma | 0.45 |
| S/N Ratio | More Than 48 dB (AGC Off) |
| Video Output | 1 Vp-p, 75 Ohms |
| Dimension (Diameter x L) | 142 x 84 mm |
| Power Supply | DC 12V (+/- 10%) |
| Storage temperature | -20°C - + 70°C |
| Operating Temperature | -10°C - + 55°C |
| Power Consumption | 110mA |
| Weight | 450g |