

WIT1035SDW

VANDAL WATER RESISTANCE IR DOME CAMERA



Features:

- Anodic Process, pants up, down and 360° side-to-side
- Patented heat radiation
- High sensitivity, true color, high resolution
- Vandal resistance
- Water resistance IP: 66

Specifications

Picture Elements HxV	NTSC/EIA: 768*494; PAL/CCIP: 753*582 (High)
H.Sync Frequency	NTSC: 15.734 KHz, PAL: 15.625 KHz
V. Sync Frequency	NTSC: 59.94 Hz, PAL: 50 Hz
Chips	1/3" Sony
Lens(mm)	6mm
Min Illumination	0.1 Lux
Resolution	480 TV Line
Synchronization	Internal
White Balance	Auto White Balance
Electronic Shutter	Auto, Rang: 1/50(1/60) – 1/100,000 sec
Gain control	Auto
Gamma	0.45
LED	35 PCS
S/N Ratio	More Than 48 dB (AGC Off)
Video Output	1 Vp-p, 75 Ohms
Dimension (Diameter x L)	94 x 78.14 mm
Power Supply	DC 12V (+/- 10%)
Storage temperature	-20°C - + 70°C
Operating Temperature	-10°C - + 55°C
Power Consumption	50mA (IR Off), 390mA(IR On)
Weight	450g